

BS-A450 Thermal Shrink Packaging Machine



BS-A450 thermal shrink packaging machine is suitable to shrink thin shrink films such as POF, PVC, PP, POP, etc. with far-infrared radiation. The thickness of shrink film should be in the range of 0.01-0.045 mm. Quartz heating pipes are located on the top, bottom and sides of the shrinking tunnel. The temperature of the shrink room and the speed of the conveyer are adjustable. And the size of shrink tunnel can be customized. Conveyor has option of chain roller and iron net conveyer for choice.

Features:

1. The lid can be open and bottom tray can be pulled out for the convenience of replacing heating pipes Compact construction, high efficiency;
2. Voltage of down heating pipes is adjustable through solid-booster, in order to control down temperature. The temperature of whole shrink tunnel is controlled through AC contactor.
3. Strong air-flow ensures excellent heat distribution for an even shrinking;
4. Intelligent temperature controlling system makes the operation easily;
5. The speed of the conveyer is adjustable.

Specification

Model	BS-A450
Voltage	380V/3PH 50-60Hz
Power	9KW
Conveyor speed	0-10m/min
Tunnel size	830x450x250mm
Heater type	Quartz heater
Heater size	370mmx15
Conveyor loading	10kg
Machine size	1200x650x1300mm



บริษัท หัวเหริยญ อินเตอร์แพ็ค จำกัด

234 ม.2 ถ.โชตนา ต.ดอนแก้ว อ.แมริม จ.เชียงใหม่ 50180

โทร.053-120222 แฟกซ์. 053-120200 มือถือ. 081-4445606

WWW.IPACK.CO.TH

E-mail: ipack.sale@gmail.com

Line ID: ipackbkk

