

# BS-G450 Thermal Shrink Packaging Machine



BS-G450 thermal shrink packaging machine is suitable to shrink thin shrink films such as POF, PVC, PP, POP, etc. with far-infrared radiation. The thickness of shrink film should be in the range of 0.01-0.04 mm. The temperature of the shrink room and the speed of the conveyer are adjustable. Furthermore, the height of shrink tunnel is able to be adjusted according to the size of packing goods. Teflon conveyor has advantage of keeping heat. It is ideal to shrink small and light box with this shrink machine.

## Features:

1. Compact construction, high efficiency;
2. Accurate temperature control of shrink tunnel.
3. Strong air-flow ensures excellent heat distribution for an even shrinking;

## Specification

Model	BS-G450
Voltage	380V/3PH 50-60Hz
Power	9KW
Conveyor speed	0-10m/min
Tunnel size	1200x450x350mm
Heater type	Steel heater
Heater size	1050mmx6
Conveyor loading	5kg
Machine size	1600x600x1300mm



บริษัท หัวเหริยญ อินเตอร์แพ็ค จำกัด

234 ม.2 ถ.โชตนา ต.ดอนแก้ว อ.แมริม จ.เชียงใหม่ 50180

โทร.053-120222 แฟกซ์. 053-120200 มือถือ. 081-4445606

WWW.IPACK.CO.TH

E-mail: [ipack.sale@gmail.com](mailto:ipack.sale@gmail.com)

Line ID: ipackbkk

