

Automatic high-speed pillow-shaped packaging machine



Performance and characteristic

- Compact structure, stable function and simple operation.
- The first third-generation double frequency control, the bag could be set and cut, unnecessary adjust air without changing film color code tracking one pace reaches the designated position, it's saving time and film.
- It adopts imported electric appliance, touch main machine interface, convenient parameter setting.
- Self-checking function ,trouble can be read easily.
- High sensor photoelectric color chart tracking, make the cutting position more correctly.
- Dependent temperature PID controlling suitable for various materials of packaging membrane.
- Position stop function, no adhesive and no waste of membrane.
- Clean rotation system, more reliable operation and more convenient maintenance.
- All the controlling operates by the software, convenience for function adjustment and technical up grading.

Main technical data

Model	KD-350			KD-450		
Finished package size	Length	Width	Height	Length	Width	Height
	(65-330mm)	(30-150mm)	(5-50mm)	(110-350mm)	(50-200mm)	(10-80mm)
Vertical and cross sealing strength	>15Nmm ²			>15Nmm ²		
Packaging speed	40-220Bags/min			40-180Bags/min		
Packaging film width	90-350mm			100-450mm		
Power specification	220V 50/60Hz 2.4KW			220V 50/60Hz 2.7KW		
Machine weight	600kg			680kg		
Overall size(L x W x H)	4100 x 1050 x 1560mm			4100 x 1050 x 1560mm		



บริษัท หัวเหรียญ อินเทอร์เน็ต จำกัด

234 ม.2 ต.ดอนแก้ว อ.แมริม จ.เชียงใหม่ 50180

โทร.053-120222 แฟกซ์. 053-120200 มือถือ. 081-4445606

WWW.IPACK.CO.TH

E-mail: ipack.sale@gmail.com

Line ID: ipackbkk

