

KD-260A Automatic reverse film packaging machine



Scope of application

Apply more material block (such as betel, olives, candied fruit, gong date) multiple packet soup, solid dispersing materials, small electronic components of irregular objects.

Performance and characteristic

- Compact structure, stable function and simple operation.
- The first third-generation double frequency control, the bag could be set and cut, unnecessary adjust air without changing film color code tracking one pace reaches the designated position, it's saving time and film.
- It adopts imported electric appliance, touch main machine interface, convenient parameter setting.
- Self-checking function ,trouble can be read easily.
- High sensor photoelectric color chart tracking, make the cutting position more correctly.
- Dependent temperature PID controlling suitable for various materials of packaging membrane.
- Position stop function, no adhesive and no waste of membrane.
- Clean rotation system, more reliable operation and more convenient maintenance.
- All the controlling operates by the software, convenience for function adjustment and technical up grading.

Main technical data

Model	KD-260A
Max.film width	260mm
Max packaging capacity(according to its material to fix)	40-250time/min
Suitable film thickness	0.03-0.06mm
Length of bags	60-200mm
Packaging width	25-100mm
Packaging height	5-45mm
Total power	2.4kw 220v
Overall dimensions(L x W x H)	4100 x 950 x 1500mm
weight	550kg



บริษัท หัวเหรียญ อินเทอร์เน็ต จำกัด

234 ม.2 ถ.โชตนา ต.ดอนแก้ว อ.แมริม จ.เชียงใหม่ 50180

โทร.053-120222 แฟกซ์. 053-120200 มือถือ. 081-4445606

WWW.IPACK.CO.TH

E-mail: ipack.sale@gmail.com

Line ID: ipackbkk

